

INK TANK SYSTEM PRINTERS

ECOTANK L15160



NOMOR MODEL

Jenis Printer

Printing

Teknologi mencetak

Konfigurasi Nozzle

Arah cetak

Maksimum Resolusi

Volume Minimum Tetesan Tinta

Kecepatan cetak

Draft Text - Memo, A4 (Hitam^{#1} / Hitam^{#2})

ISO 24734, A4 (Hitam/Warna)

ISO 24734, A3 (Hitam/Warna)

Waktu keluar halaman pertama (Hitam/Warna), A4

Photo Default - 10 x 15 cm / 4 x 6" ^{7.49} (Border / Borderless)

Bahasa Printer

Automatic 2- Pencetakan Sisi

Spesifikasi Elektrik

Nilai Tegangan

Nilai Frekuensi

Konsumsi Daya

Operating

Standby

Sleep

Daya Mati

L15160

Cetak, Pindai, Salin, Fax dengan AOF

PrecisionCore™ Printhead

800 x 1 Masing masing nozzle (Hitam, Cyan, Magenta, Kuning)

Bi-Pencetakan directional

4800 x 1200 dpi

3.8 pl

Hingga 32.0 ppm / 32.0 ppm

Simplex: Hingga 25.0 ipm / 25.0 ipm | Duplex: Hingga 21.0 ipm / 21.0 ipm

Simplex: Hingga 13.5 ipm / 13.5 ipm | Duplex: Hingga 10.0 ipm / 10.0 ipm

Simplex: Hingga 5.5 detik / 5.5 detik | Duplex: 11.0 detik / 11.5 detik

Approx. 26 detik per photo (Border) / 27 detik per photo (Borderless)

ESC/P-R, ESC/P Rater

Yes (Hingga A3)

AC 220 - 240 V

50 - 60 Hz

18.0 W

9.7 W

0.9 W

0.2 W

L15160

Dimensi & berat
Berat: 21,0 kg



Rental Multifuntion Printer



021 - 5658989



0818 07752219



0812 70925845